



- 1 Install structural supports perpendicular with *SHERA* Floor Plank's direction spacing not more than 40 cm apart.
- 2 Fasten *SHERA* Floor Plank with screw at at 1.2 cm. from the long-side edges and 1-2 cm. from both wide-side edges.
- 3 Caulk the screw heads before applying touch-up paints for colored floor plank.
For Pre-primed *SHERA* Floor Plank, make sure the surface is cleaned before applying decking paint.
- 4 For Clip-lock *SHERA* Floor Plank series, fasten the first plank to steel stud with screw at 5 cm. from the edge.
Align *SHERA* Clip-Lock to the other side of the plank with one of its wing slotted into the plank's groove.
Screw the clip-lock to the steel studs holding the plank in place.

Handling & storage



SHERA products should be handled and stacked carefully to avoid damages to their edges and corners.

The maximum height of stack is 1 meter with timber bearers supported at every 50 cm.



SHERA products should be stacked on dry and leveled ground.

It is recommended to store *SHERA* under shade to prevent damages that could occur to the product in case of prolonged exposure to high humidity environment prior to installation.



During a transfer, *SHERA* products should be handled at 50 cm. from both ends.

The product should be lifted such that its side is parallel to the floor.

Avoid installing *SHERA* product under wet condition to reduce chance of cracking.