

# TEST REPORT



Your Ref:

Date: 06 Oct 2006

Our Ref: 54S065688/B/EMK

Page: 1 of 8

DID: + 65-6885 1438

Fax: + 65-6779 3903

**NOTE:** This report is issued subject to PSB Corporation's "Terms and Conditions Governing Technical Services".  
The terms and conditions governing the issue of this report are set out as attached within this report.

## **SUBJECT:**

Laboratory measurement of airborne sound transmission loss of "SHERA" Cellulose fiber partition panel system submitted by Mahaphant Fibre-Cement Public Co., Ltd on 22 Aug 2006.

## **TESTED FOR:**

Mahaphant Fibre-Cement Public Co., Ltd  
99 Moo 12 Saraburi-Lomsak Road  
K.M. 16, Chongsarika,  
Lopburi 15220 Thailand

Attn: Mr Ekarat Unkammuang

## **DATE OF TEST:**

2 Oct 2006

## **DESCRIPTION OF SAMPLE:**

A "SHERA" Cellulose fiber partition panel system, STC 60 was installed onto the sample carrier by two sub-contractors, Lively House Interiors & Trading and Tarlic Engineering Construction.

Tarlic Engineering Construction was in-charge for the installation of the C-channel frame structure and "Shera Flexy" board. Lively House Interiors & Trading was in-charge of the spraying of the cellulose fiber material onto the sample after the board.

The "SHERA" Cellulose fiber partition panel system consisted of the following layers. The 10mm thick "SHERA" Flexy board was used as two outer layers and one inner layer in the construction. Two layers of 74mm thick Cellulose fiber materials were placed between the adjacent boards.

The mass of a randomly selected pitch area of 0.6m (width) x 0.59m (length) x 0.074m (thick) of cellulose fiber material was 2.8kg. The calculated density of the cellulose fiber material used for the test was 107kg/m<sup>3</sup>.

The technical specification of the system layout was shown in Appendix.



A handwritten signature in black ink, appearing to be 'R. S. S.' or similar.

**METHOD OF TEST:**

The test was conducted in accordance with ASTM E90 - 97 "Standard test method for laboratory measurement of airborne sound transmission loss of building partitions and elements"

Measured area of system opening : 3.19m (width) x 3.16m (height) = 10.08m<sup>2</sup>

Air temperature in both source room and receiving room : 25°C

Relative air humidity in both source room and receiving room : 55%

Source room volume : 72m<sup>3</sup>


Receiving room volume : 86m<sup>3</sup>

Location of the test : Acoustics Lab of PSB Corporation Pte Ltd

**TEST EQUIPMENT:**


The following instruments were used for the test.

- 1) A dual-channel real-time frequency analyser (B&K Type 2133)
- 2) An Omni-loudspeaker (B&K Type 4296)
- 3) Two sets of ½" condenser microphones (B&K Type 4190)
- 4) Two sets of microphone preamplifiers (B&K Type 2669)
- 5) A sound pressure level calibrator (Norsonic Type 1251)
- 6) A sound source amplifier (Crown model CE 1000)
- 7) Two sets of rotating microphone booms (B&K Type 3923)



**TEST PROCEDURES:**

- 1) Instrumentation was set up according to ASTM E90-97
- 2) Measurement system was calibrated using a sound level calibrator Norsonic Type 1251.
- 3) Background noise level for both source room and receiving room were measured.
- 4) Sound source system was switched on and maintained at constant level. The sound pressure level in the receiving room was ensured to be 15dB higher than the background noise level.
- 5) Recording time for both rotating microphone booms was set to 64s which equals to the time taken by the booms to complete two revolutions.
- 6) Sound pressure level difference between the source room and the receiving room was measured with a dual – channel acoustic analyser (B&K 2133), and the measurement was repeated 3 times.
- 7) Step 6 was repeated after the loudspeaker was moved to new position.
- 8) Reverberation time (RT) of the receiving room was measured from two different loudspeaker positions. Each loudspeaker position was measured 2 times.
- 9) The mean values of the six readings for sound pressure level difference and four readings for RT values were calculated.
- 10) Values of sound transmission loss were determined for each 1/3 octave frequency band from 100Hz to 5kHz based on the mean values of step 9.
- 11) Sound transmission class was determined at the frequency of 500Hz of the shifted reference curve according to ASTM E 413.



**RESULTS:**

Values of sound transmission loss (TL) of the sample tested were tabulated in Table 1. Sound insulation rating was computed according to ASTM E413 - 87 (Reapproved 1999) "Classification for rating sound insulation".

**Table 1 : Measured values of TL and values of the shifted reference curve for STC = 64**

| 1/3 Octave Band Frequency (Hz)             | TL (dB) | STC = 64 (dB) | Deficiency |
|--|---------|---------------|------------|
| 100  | 31      | 45            | 14         |
| 125  | 40      | 48            | 8          |
| 160  | 46      | 51            | 5          |
| 200  | 49      | 54            | 5          |
| 250  | 55      | 57            | 2          |
| 315  | 58      | 60            | 2          |
| 400  | 65      | 63            | 0          |
| 500  | 68      | <b>64</b>     | 0          |
| 630  | 69      | 65            | 0          |
| 800  | 70      | 66            | 0          |
| 1000                                       | 72      | 67            | 0          |
| 1250                                       | 73      | 68            | 0          |
| 1600                                       | 73      | 68            | 0          |
| 2000                                       | 73      | 68            | 0          |
| 2500                                       | 67      | 68            | 1          |
| 3150                                       | 63      | 68            | 5          |
| 4000                                       | 68      | 68            | 0          |
| 5000                                       | 73      | 68            | 0          |
| <b>Total deficiency (125Hz – 4000Hz) :</b> |         |               | <b>28</b>  |


The values in Table 1 were plotted as shown in Figure 1.

**Remarks:**

- 1) Each layer of cellulose fiber material was cured for 8 days, and a total of 16 days were used to ensure that it was sufficiently dry for test.
- 2) The tested sample has a sound transmission class, STC = 64





Ee Min Kuen  
Testing Officer



Dr Sun Qiqing  
Assistant Vice President  
Acoustic & Vibration/Packaging

**RESULTS: (cont'd)**

**Figure 1: Sound insulation performance of "SHERA" Cellulose partition panel system, STC 64**


**RESULTS: (cont'd)**




**Figure 2 : Test set up of sample in the source room**



**Figure 3 : Test set up of sample in the receiving room**



Appendix



**This Report is issued under the following conditions:**

1. Results of the testing/calibration in the form of a report will be issued immediately after the service has been completed or terminated.
2. Unless otherwise requested, a report shall contain only technical results. Analysis and interpretation of the results and professional opinion and recommendations expressed thereupon, if required, shall be clearly indicated and additional fee paid for, by the Client.
3. This report applies to the sample of the specific product/equipment given at the time of its testing/calibration. The results are not used to indicate or imply that they are applicable to other similar items. In addition, such results must not be used to indicate or imply that PSB Corporation approves, recommends or endorses the manufacturer, supplier or user of such product/equipment, or that PSB Corporation in any way "guarantees" the later performance of the product/equipment.
4. The sample/s mentioned in this report is/are submitted/supplied/manufactured by the Client. PSB Corporation therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture, consignment or any information supplied.
5. Additional copies of the report are available to the Client at an additional fee. No third party can obtain a copy of this report through PSB Corporation, unless the Client has authorised PSB Corporation in writing to do so.
6. PSB Corporation may at its sole discretion add to or amend the conditions of the report at the time of issue of the report and such report and such additions or amendments shall be binding on the Client.
7. All copyright in the report shall remain with PSB Corporation and the Client shall, upon payment of PSB Corporation's fees for the carrying out of the tests/calibrations, be granted a license to use or publish the report to the third parties subject to the terms and conditions herein, provided always that PSB Corporation may at its absolute discretion be entitled to impose such conditions on the license as it sees fit.
8. Nothing in this report shall be interpreted to mean that PSB Corporation has verified or ascertained any endorsement or marks from any other testing authority or bodies that may be found on that sample.
9. This report shall not be reproduced wholly or in parts and no reference shall be made by the Client to PSB Corporation or to the report or results furnished by PSB Corporation in any advertisements or sales promotion.
10. Unless otherwise stated, the tests are carried out in PSB Corporation Pte Ltd, No.1 Science Park Drive Singapore 118221.

June 2006